

Accessories

Earphones		6
EP-830	Single Earphone (can be disassembled, TRS connector, Ring: NC).....	6
EP-820AS	Single Earphone (TRS connector, Ring: NC).....	6
EP-822	Single Inner Earphone (TRS connector, Ring: NC).....	6
EP-823L	Single Earphone (left, TRS connector, Ring: NC).....	6
EP-823R	Single Earphone (right, TRS connector, Ring: NC).....	7
EP-829	Single Earphone (ear pads can be striped, TRS connector, Ring: NC).....	7
EP-960AN	Interpreter Headset(TRRS plug, stereo, for HCS-8385/80, including a pair of EP-960HD Detachable Earshells).....	7
EP-960AH	Interpreter Headset(stereo, for HCS-4385U/50, including a pair of EP-960HD Detachable Earshells)...	8
EP-960BH	Interpreter Headphones (stereo, including a pair of EP-960HD Detachable Earshells).....	8
HCS-5100PA	Interpreter Headphones.....	8
HCS-5100PA-PAD	Sponge Ear Pads (thick, for HCS-5100PA, 50 pairs/package).....	9
EP-960SP-L	Sponge Ear Pads for EP-960 (Ø 70 mm, for EP-960AH/EP-960BH, 10 pairs/package).....	9
EP-960SP-S	Sponge Ear Pads for EP-960 (Ø 58 mm, for EP-960AH/EP-960BH, 10 pairs/package).....	9
EP-960HD	Detachable Earshells for EP-960 (for EP-960AH/EP-960BH, 1 pair).....	9
HCS-1020 Clip Microphone		9
Stem Microphones		10
MS33EGF1S	Stem Microphone (33 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, silver).....	10
MS33EGF1B	Stem Microphone (33 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, black).....	10
MS41EGF1S	Stem Microphone (41 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, silver).....	10
MS41EGF1B	Stem Microphone (41 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, black).....	10
MS47EGF1S	Stem Microphone (47 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, silver).....	10
MS47EGF1B	Stem Microphone (47 cm, semi-rigid gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, black).....	10
MS50EGF2B	Stem Microphone (50 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	11
MS60EGF2B	Stem Microphone (60 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	11

MS70EGF2B	Stem Microphone (70 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	11
MS33EGFSS	Stem Microphone (33 cm, fully flexible gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for interpreter unit, silver).....	12
MS33EGFSB	Stem Microphone (33 cm, fully flexible gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-9385 RSI interpreter unit, black).....	12
MS33EHA1B	Stem Microphone (33 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	13
MS41EHA1B	Stem Microphone (41 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	13
MS47EHA1B	Stem Microphone (47 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black).....	13
MIC-CAMP_G	Lockable Windshield (for MS**EGF series stem microphone, optional, gray).....	14
MIC-CAMP_B	Lockable Windshield (for MS**EGF series stem microphone, optional, black).....	14
MIC-SK-V	Stem Microphone Fixing Base (tabletop).....	14
Battery and Charging Devices		15
HCS-5300BAT	Lithium Rechargeable Battery Pack (11.1 V DC, for HCS-5300/01/02 series conference unit).....	15
HCS-5300CHG/08	Charging Unit (8 pcs/case, for HCS-5300BAT).....	15
HCS-5300CHG/06	Charging Unit (6 pcs/case, for HCS-5380 series, HCS-5381C/D, 5381RC/RD conference unit).....	16
HCS-5300CHG/06A	Charging Unit (6 pcs/case, for HCS-5380 series, HCS-5381RC/RD conference unit).....	16
Power Adapter		17
HCS-ADP15V	Power Adapter (15 V DC, 2.4 A, for HCS-5300/01/02 series conference unit).....	17
HCS-ADP24V	Power Adapter (24 V DC, 1.5 A, for HCS-5300TH).....	17
HCS-ADP24V2	Power Adapter (24 V DC, 1.5 A, for HCS-5300TWN).....	18
HCS-ADP48V	Power Adapter (48 V DC, 1.875 A, for HCS-8368T/50, HCS-8685BM).....	18
TES-ADP5V	Power Adapter (5 V DC, 2.0 A, for HCS-5380/5381 series conference unit).....	19
Cables and Connectors		20
CBL2SS-01	1 m 2-pin Cable (with two sockets).....	20
CBL2SS-01CMP	1 m 2-pin Cable (with two sockets, CMP).....	20
CBL4PK-01CMP	1 m Power Adapter Cable (for device supplies power to HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638, CMP).....	20
CBL4PS-05CMP	5 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4PS-10CMP	10 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4PS-20CMP	20 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4PS-30CMP	30 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4PS-40CMP	40 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4PS-50CMP	50 m 4-pin Extension Cable (with a plug and a socket, CMP).....	20
CBL4C-CMP	Professional Extension Cable for Conference System (4-pin, 18AWGx4C, CMP).....	21
CBL4PT-02ACMP	2 m Power Branch Cable (for HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638 series Paperless Multi-media Congress Terminal, CMP).....	21

CBL5-UTP	Professional Extension Cable for Conference System.....	21
CBL5-FTP-CMP	Professional Extension Cable for Conference System (CMP).....	21
CBL6PP-02	2 m 6-pin Extension Cable (with two plugs).....	21
CBL6PP-02CMP	2 m 6-pin Extension Cable (with two plugs, CMP).....	21
CBL6PS-01	1 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-03	3 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-05	5 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-10	10 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-20	20 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-30	30 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-40	40 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-50	50 m 6-pin Extension Cable (with a plug and a socket).....	22
CBL6PS-03CMP	3 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-05CMP	5 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-10CMP	10 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-20CMP	20 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-30CMP	30 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-40CMP	40 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL6PS-50CMP	50 m 6-pin Extension Cable (with a plug and a socket, CMP).....	22
CBL5300-05	5 m Dedicated Transceiver Cable.....	22
CBL5300-10	10 m Dedicated Transceiver Cable.....	22
CBL5300-20	20 m Dedicated Transceiver Cable.....	22
CBL5300-30	30 m Dedicated Transceiver Cable.....	22
CBL5300-40	40 m Dedicated Transceiver Cable.....	22
CBL5300-50	50 m Dedicated Transceiver Cable.....	22
CBL5300-05CMP	5 m Dedicated Transceiver Cable (CMP).....	22
CBL5300-10CMP	10 m Dedicated Transceiver Cable (CMP).....	22
CBL5300-20CMP	20 m Dedicated Transceiver Cable (CMP).....	22
CBL5300-30CMP	30 m Dedicated Transceiver Cable (CMP).....	22
CBL5300-40CMP	40 m Dedicated Transceiver Cable (CMP).....	22
CBL5300-50CMP	50 m Dedicated Transceiver Cable (CMP).....	22
CBLRG-59	Coaxial-cable (75 Ω, Ø 5 mm) (unit: meter).....	23
CBLRG-6/U	Coaxial-cable (75 Ω, Ø 7 mm) (unit: meter).....	23
CBL8PS-01	1 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-03	3 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-05	5 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-10	10 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-20	20 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-30	30 m 8-pin Extension Cable (with a male plug and a female plug).....	23

CBL8PS-40	40 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PS-50	50 m 8-pin Extension Cable (with a male plug and a female plug).....	23
CBL8PP-02	2 m 8-pin Extension Cable (with two male plugs).....	24
CBL-8P2RJ45S-01	1 m 8-pin to RJ45 converter cable (with a 8-pin male plug and a RJ45 socket, cat.5 Extension Cable	25
CBL-8S2RJ45S-01	1 m 8-pin to RJ45 converter cable (with a 8-pin female plug and a RJ45 socket, cat.5 Extension Cable with drain wire).....	25
CBLRJ45-02	2 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-05	5 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-10	10 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-20	20 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-30	30 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-40	40 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLRJ45-50	50 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs).....	26
CBLCAT5E	Cat.5e Extension Cable (with drain wire, 305 m per roll, unit: meter).....	26
RJ45-PLUG	Shielded RJ45 plug.....	26
BNC-M	BNC Connector (plug).....	27
HCS-4352T/50	6-pin Cable Splitter (1 input & 3 outputs, for HCS-4100/50 and HCS-8300 series).....	27
HCS-5352	Cable Splitter (1 input & 4 outputs, for HCS-5300T series).....	27
HCS-4353N/06	6-pin Grounding Cable Connection Socket (for HCS-3900, HCS-4100/50 and HCS-8300 series).....	28
DIN-6PM	Detachable 6-pin Standard Plug (male).....	28
DIN-6PF	Solderable 6P-DIN Standard Socket (female) (insulating).....	28
DIN-4PM	Detachable 4-pin Standard Plug(male).....	28
DIN-4PF	Detachable 4-pin Standard Socket (female).....	29
DIN-4SF	Solderable 4P-DIN Standard Socket (insulating).....	29
DIN-8PM	Detachable 8P-DIN Standard Plug(male).....	29
DIN-8PF	Detachable 8P-DIN Standard Socket (female).....	29
DIN-8SF	Solderable 8P-DIN Standard Socket (insulating).....	29
HCS-4345TK/50	Touched IC-Card Encoder (champagne panel + gray base).....	30
HCS-5300TJ2	Transceiver Stand (for HCS-5300TD/ HCS-5300TH / HCS-5390M).....	30
HCS-MES-RCF	Rack Cabinet Frame (1 HCS-8600MES, 1 HCS-8300MES or 1 HCS-3900MES Extension Unit can be installed).....	31
Multifunctional Storage Case.....		32
HCS-852KS	Multifunctional Storage Case(inner height 620 mm, free fit Foam Insert, holds up to 24 stem microphones in the case cover).....	32
HCS-852S-CMU	Foam Insert (for 1 pc main unit with 2U high + 20 m extension cable).....	32
HCS-852S-DStyle	Foam Insert (for 12 pcs HCS-4330/32 + 8 pcs stem microphones).....	33
HCS-852S-GStyle	Foam Insert (for 10 pcs HCS-4886/87/88 + 6 pcs stem microphones).....	33
HCS-852S-1U	Foam Insert (for 2 pcs units of 1U height and attached cables).....	34
HCS-852S-4338	Foam Insert(for 16 pcs HCS-4338/HCS-3938 + 10 pcs stem microphones + attached cables).....	34
HCS-852S-4385U	Foam Insert (for 6 pcs HCS-4385U/50 + 2 pcs stem microphones).....	35
HCS-852S-5100T	Foam Insert (for 1 pc HCS-5100T+ 2 pcs HCS-4385U/50).....	35

HCS-852S-5300CHG	Foam Insert (for 2 pcs HCS-5300CHG/08).....	36
HCS-852S-5300D	Foam Insert (for 8 pcs 5300 wireless conference units).....	36
HCS-852S-5300TD	Foam Insert (for 1 pc HCS-5300CHG/08 + 2 pcs HCS-5300TD).....	37
HCS-852S-8338	Foam Insert (for 4 pcs HCS-8338/HCS-8335/HCS-8336 series Congress Terminals).....	37
HCS-852S-4860	Foam Insert (for 8 pcs HCS-4860 series congress units).....	38
HCS-852S-4866	Foam Insert (for 8 pcs HCS-4866/50 series congress units).....	38
HCS-852S-4890	Foam Insert (for 12 pcs HCS-4890/50 series congress units + 12 pcs stem microphones).....	39
HCS-852S-4891R	Foam Insert (for 8 pcs HCS-4891R/50/(2M) series congress units).....	39
HCS-852S-8368A	Foam Insert (for 5 pcs HCS-8368A/50 series tabletop Congress Terminals).....	40
HCS-852S-8385	Foam Insert (for 6 pcs HCS-8385/80 interpreter units).....	40
HCS-853KS	Transport Cabinet (inner height 15U).....	41
HCS-854KS	Portable Multifunctional Storage Case (inner height 299 mm, free fit Foam Insert).....	42
HCS-854S-CMU	Foam Insert (for 1 pc main unit with 2U high).....	43
HCS-854S-MIC	Foam Insert (for 11 stem microphones).....	43
HCS-854S-4338	Foam Insert (for 10 pcs HCS-4338).....	44
HCS-854S-4385U	Foam Insert (for 3 pcs HCS-4385U/50 + 4 pcs stem microphones).....	44
HCS-854S-4886	Foam Insert (for 3 pcs HCS-4886/87/88 + 4 pcs stem microphones).....	45
HCS-854S-5100T	Foam Insert (for 1 pc HCS-5100T).....	45
HCS-854S-5300	Foam Insert (for 4 pcs HCS-5300 wireless conference units + 4 pcs stem microphones).....	46
HCS-854S-8338	Foam Insert (for 3 pcs HCS-8338/HCS-8335/HCS-8336 series Congress Terminals).....	46

Interpreter Booth and Shipping Case

HCS-851A/02	Interpreter Booth (accommodates 2 interpreters, internal dimensions is 200×160×160 cm, aluminum alloy framework convenience for disassembly, with a shipping case, total weight is 260 kg).....	48
HCS-851K	Interpreter Booth Shipping Case (for HCS-851A/02).....	48
HCS-851A/03	Interpreter Booth (accommodates 3 interpreters, internal dimensions is 200×240×160 cm, aluminum alloy framework convenience for disassembly, with 2 shipping case, total weight is 350 kg).....	49
HCS-851KT	Interpreter Booth Shipping Case (for HCS-851A/03, HCS-851K needed).....	49

EP-830 Single Earphone



Features

- Used with interpretation receiver or on a conference unit
- Hi-Fi sound quality
- Assembled with detachable shell, cable and earphone
- The shell can be removed and cleaned separately
- The cable can be replaced separately by customer if breaks
- Ø 3.5 mm stereo plug (TRS)
- 32 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW
- Weight: ≤25 g

Ordering Information

EP-830.....Single Earphone (can be disassembled, TRS connector, Ring: NC)

EP-820AS Single Earphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- Ø 3.5 mm stereo plug (TRS)
- 32 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 50 Hz to 20 kHz
- Sensitivity: ≥102 dBA/1 mW
- Weight: 20 g

Ordering Information

EP-820AS.....Single Earphone (TRS connector, Ring: NC)

EP-822 Single Inner Earphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- Ø 3.5 mm stereo plug (TRS)
- 16 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥90 dBA/1 mW
- Weight: 7 g

Ordering Information

EP-822.....Single Inner Earphone
(TRS connector, Ring: NC)

EP-823L Single Earphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- For the left ear
- Ø 3.5 mm stereo plug (TRS)
- 32 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥103 dBA/1 mW
- Weight: 20 g

Ordering Information

EP-823L.....Single Earphone (left, TRS connector, Ring: NC)

EP-823R Single Earphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- For the right ear
- Ø 3.5 mm stereo plug (TRS)
- 32 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥103 dBA/1 mW
- Weight: 20 g

Ordering Information

EP-823L.....Single Earphone (right, TRS connector, Ring: NC)

EP-829 Single Earphone



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- Earshell is detachable and washable, convenient for cleaning
- Ø 3.5 mm stereo plug (TRS)
- 32 Ohm (Tip and Sleeve, Ring: NC)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW
- Weight: 35 g

Ordering Information

EP-829.....Single Earphone (ear pads can be striped, TRS connector, Ring: NC)

EP-960AN Interpreter Headset



Features

- Incorporated with interpreter unit for monitoring and speaking
- Excellent sound quality
- Interpreters can wear the headset according to their habits
- One sided wire, provide better user experience
- Greater headband adjustability, suitable for all the users
- 150 Ohm x 2, Ø 3.5 mm TRRS plug
- Frequency response of headphone: 20 Hz to 20 kHz
- Sensitivity of headphone: ≥108 dBA/1 mW
- Polar pattern of microphone: Omnidirectional
- Frequency response of microphone: 50 Hz to 20 kHz
- Sensitivity of microphone: -48 dBV/Pa
- Impedance of microphone: <680 Ohm
- Weight: 95 g

Ordering Information

EP-960AN.....Interpreter Headset (TRRS plug, stereo, for HCS-8385/80, including a pair of EP-960HD Detachable Earshells)

EP-960AH Interpreter Headset



Features

- Incorporated with interpreter unit for monitoring and speaking
- Excellent sound quality
- Interpreters can wear the headset according to their habits
- One sided wire, provide better user experience
- Greater headband adjustability, suitable for all the users
- 150 Ohm × 2, Ø 3.5 mm stereo plug (TRS) for headphone
- Ø 3.5 mm stereo plug (TRS, Ring: NC) for microphone
- Frequency response of headphone: 20 Hz to 20 kHz
- Sensitivity of headphone: ≥108 dBA/1 mW
- Polar pattern of microphone: Omnidirectional
- Frequency response of microphone: 50 Hz to 20 kHz
- Sensitivity of microphone: -48 dBV/Pa
- Impedance of microphone: <680 Ohm
- Weight: 109 g

Ordering Information

EP-960AH.....Interpreter Headset (stereo, for HCS-4385U/50, including a pair of EP-960HD Detachable Earshells)

EP-960BH Interpreter Headphones



Features

- Incorporated with interpreter unit for monitoring
- Excellent sound quality
- One sided wire, provide better user experience
- Greater headband adjustability, suitable for all the users
- 150 Ohm × 2, Ø 3.5 mm stereo plug (TRS) for headphone
- Frequency response of headphone: 20 Hz to 20 kHz
- Sensitivity of headphone: ≥108 dBA/1 mW
- Weight: 90 g

Ordering Information

EP-960BH.....Interpreter Headphones (stereo, including a pair of EP-960HD Detachable Earshells)

HCS-5100PA Headphones



Features

- Used with the receiver or a conference unit
- Excellent sound quality
- 32 Ohm × 2, Ø 3.5 mm stereo plug (TRS)
- Frequency response: 20 Hz to 20 kHz
- Sensitivity: ≥108 dBA/1 mW
- Weight: 70 g

Ordering Information

HCS-5100PA.....Headphones

Sponge Ear Pads



Features

- Used for headphone
- 50 pairs per package
- Color: black

Ordering Information

HCS-5100PA-PAD.....Sponge Ear Pads (thick, for new HCS-5100PA, 50 pairs/package)

EP-960SP-L.....Sponge Ear Pads (Ø 70 mm, for EP-960 series headset, 10 pairs/package)

EP-960SP-S.....Sponge Ear Pads (Ø 58 mm, for EP-960 series headset, 10 pairs/package)

EP-960HD Detachable Earshells



Features

- Used for EP-960 series headset
- Earshell is detachable and washable, convenient for cleaning
- Color: black

Ordering Information

EP-960HD.....Detachable Earshells for EP-960 (for EP-960 series headset, 1 pair)

HCS-1020 Clip Microphone



Features

- Stylish and ergonomic design
- Excellent immunity to RF interferences from mobile phones
- Ø 3.5 mm stereo plug with a 1.5-meter cable

Technical Specifications

Electrical

Transducer..... Electret-condenser

Polar pattern..... Uni-directional

Operating voltage..... 5 VDC

Sensitivity..... -46 dBA at 680 Ohm (0 dB = 1 V/Pa at 1 kHz)

Frequency response..... 30 Hz to 20 kHz

Input impedance..... 2 kOhm

Directivity 0°/180°..... > 20 dB (1 kHz)

Equivalent noise..... 20 dBA (SPL)

Maximum sound pressure level..... 125 dB (THD<3%)

Mechanical

Dimensions (h x w x d)..... 51 x 25 x 13 mm

Weight..... 3 g

Color..... Black

Ordering Information

HCS-1020.....Clip Microphone


MSxxEGF2B Stem Microphone




Features

- With dual-flex gooseneck arm
- Broadcast quality microphone
- With bi-color illuminated ring (green/red)
- With lockable windshield
- For HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series Congress Unit
- Optional

Polar pattern



Frequency response



Technical Specifications

Electrical

Transducer..... Electret-condenser
 Polar pattern..... Uni-directional
 Operating voltage..... 5 VDC
 Sensitivity..... -46 dBA at 680 Ohm (0 dB = 1 V/Pa at 1 kHz)
 Frequency response..... 50 Hz to 20 kHz
 Input impedance..... 2 kOhm
 Directivity 0°/180°..... > 20 dB (1 kHz)
 Equivalent noise..... 20 dBA (SPL)
 Maximum sound pressure level..... 125 dB (THD<3%)

Mechanical

Length..... 50 cm, 60 cm, 70 cm
 Color..... Black (PANTONE 419 C)

Ordering Information

- MS50EGF2B..... Stem Microphone (50 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)
- MS60EGF2B..... Stem Microphone (60 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)
- MS70EGF2B..... Stem Microphone (70 cm, dual-flex gooseneck arm, broadcast quality microphone, with bi-color illuminated ring and lockable windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)


MSxxEHA1B Stem Microphone




Features

- With semi-rigid gooseneck arm
- Broadcast quality microphone
- 14 mm uni-directional electret condenser microphone
- With bi-color illuminated ring (green/red)
- With windshield
- For HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series Congress Unit
- Optional

Polar pattern



Frequency response



Technical Specifications

Electrical

Transducer..... Electret-condenser
 Polar pattern..... Uni-directional
 Operating voltage..... 5 VDC
 Sensitivity..... -38 dBA at 680 Ohm (0 dB = 1 V/Pa at 1 kHz)
 Frequency response..... 50 Hz to 20 kHz
 Input impedance..... 2 kOhm
 Directivity 0°/180°..... > 20 dB (1 kHz)
 Equivalent noise..... 20 dBA (SPL)
 Maximum sound pressure level..... 110 dB (THD<3%)

Mechanical

Length..... 33 cm, 41 cm, 47 cm
 Weight..... 110 g, 117 g, 124 g
 Color..... Black (PANTONE 419 C)

Ordering Information

MS33EHA1B..... Stem Microphone (33 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)

MS41EHA1B..... Stem Microphone (41 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)

MS47EHA1B..... Stem Microphone (47 cm, semi-rigid gooseneck arm, broadcast quality microphone, 14 mm uni-directional electret condenser microphone, with bi-color illuminated ring and windshield, for HCS-4100, HCS-4800, HCS-5300, HCS-8300 and HCS-8600 series, optional, black)

MIC-CAPM Windshield - lockable



Features

- Lockable windshield
- For MS**EGF series stem microphone
- Optional
- Color: gray (PANTONE 446 C) / black (PANTONE 419 C)

Ordering Information

MIC-CAPM_G Lockable Windshield
 (for MS**EGF series stem microphone, optional, gray)

MIC-CAPM_B Lockable Windshield
 (for MS**EGF series stem microphone, optional, black)

MIC-SK-V Stem Microphone Fixing Base



Features

- Fix 5P E type stem microphone on the desk
- 6P mini DIN interface with 1.0-meter cable

Technical Specifications

Mechanical

Dimensions (diameter x h) Ø 50 x 22 mm

Weight 0.1 kg

Color Brown (PANTONE 1685 U)

Ordering Information

MIC-SK-V Stem Microphone Fixing Base (tabletop)

HCS-5300BAT Lithium Rechargeable Battery Pack



Features

- Lithium rechargeable battery pack
- Used for supplying power to HCS-5300/80 series digital infrared wireless conference unit

Technical Specifications

Electrical

Nominal voltage.....11.1 V DC
Nominal capacity.....4400 mAh

Mechanical

Dimensions (h x w x d).....28 x 140 x 58 mm
Weight.....0.3 kg
Color.....Black

Ordering Information

HCS-5300BAT.....Lithium Rechargeable Battery Pack
(11.1 V DC, for HCS-5300/01/02 series conference unit)

HCS-5300CHG/08 Charging Unit



Features

- Used for charging HCS-5300BAT Lithium batteries
- Charges 8 pcs of HCS-5300BAT batteries per charging
- Uses universal power supply with automatic voltage matching

Controls and Indicators

- Power switch
- Charging indicator (red)
- Fully charged indicator or battery not inserted (green)

Interconnections

- Power output interface
- Power input interface
- Charging lattices

Technical Specifications

Electrical

Power supply.....AC 100 V -240 V 50 Hz/60 Hz
Power consumption.....Max. 380 W
Charging time.....Approx 6 hours
Charging capacity.....8 HCS-5300BAT batteries

Mechanical

Dimensions (h x w x d).....74 x 288 x 300 mm
Weight.....4.5 kg
Color.....White

Ordering Information

HCS-5300CHG/08.....Charging Unit (8 pcs/case,
for HCS-5300BAT)

HCS-5300CHG/06 Charging Unit



Features

- Used for charging HCS-5380/81 series wireless unit
- Charges 6 pcs of HCS-5380 series, HCS-5381C/D and HCS-5381RC/RD units per charging
- Power supply: 9 VDC, 6 A adapter

Controls and Indicators

- Charging indicator
- Power indicator

Technical Specifications

Electrical

Power supply9 VDC, 6 A adapter
 Power consumption.....Max. 50 W
 Charging time.....Approx 4 hours
 Charging capacity.....6 HCS-5380 units

Mechanical

Dimensions (h x w x d).....21 x 448 x 316 mm
 Weight.....0.4 kg
 Color.....Black

Ordering Information

HCS-5300CHG/06.....Charging Unit (6 pcs/case, for
 HCS-5380 series,
 HCS-5381C/D and
 HCS-5381RC/RD units)

HCS-5300CHG/06A Charging Unit



Features

- Used for charging HCS-5380 and HCS-5381 series (w/o. HCS-5381R series) wireless unit
- Charges 6 pcs of HCS-5380 series units, HCS-5381C/D and per charging, HCS-5381RC/RD units is unavailable
- Power supply: 9 VDC, 6 A adapter

Controls and Indicators

- Charging indicator
- Power indicator

Technical Specifications

Electrical

Power supply.....9 VDC, 6 A adapter
 Power consumption.....Max. 50 W
 Charging time.....Approx 4 hours
 Charging capacity.....6 HCS-5380 units

Mechanical

Dimensions (h x w x d).....21 x 448 x 316 mm
 Weight.....0.4 kg
 Color.....Black

Ordering Information

HCS-5300CHG/06A.....Charging Unit (6 pcs/case, for
 HCS-5380 series,
 HCS-5381C/D (w/o.
 HCS-5381R series)
 conference unit)

HCS-ADP15V Power Adapter



Features

- Used for supplying power to HCS-5300/80 series digital infrared wireless conference unit

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....15 V DC, 2.4 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....3 m
 Dimensions (h x w x d).....28 x 95 x 45 mm
 Weight.....0.3 kg
 Color.....Black

Ordering Information

HCS-ADP15V.....Power Adapter (15 V DC, 2.4 A,
 for HCS-5300/01/02 series
 conference unit, HCS-8319N)

HCS-ADP24V Power Adapter



Features

- Used for supplying power to HCS-5300TH/80 Digital Infrared Transceiver

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....24 V DC, 1.5 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....3 m
 Dimensions (h x w x d).....28 x 95 x 45 mm
 Weight.....0.3 kg
 Color.....Black

Ordering Information

HCS-ADP24V.....Power Adapter (24 V DC, 1.5 A,
 for HCS-5300TH)

HCS-ADP24V2 Power Adapter



Features

- Used for supplying power to HCS-5300TWN Digital Infrared Transceiver

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....24 V DC, 1.5 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....3 m
 Dimensions (h x w x d).....28 x 95 x 45 mm
 Weight.....0.3 kg
 Color.....Black

Ordering Information

HCS-ADP24V2.....Power Adapter (24 V DC, 1.5 A,
 for HCS-5300TWN)

HCS-ADP48V Power Adapter



Features

- Used for supplying power to HCS-8368T/50

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....48 V DC, 1.875 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....3 m
 Dimensions (h x w x d).....33 x 150 x 62 mm
 Weight.....0.5 kg
 Color.....Black

Ordering Information

HCS-ADP48V.....Power Adapter (48 V DC, 1.875 A,
 for HCS-8368T/50, HCS-8685BM)

TES-ADP5V Power Adapter



Features

- Used for charging HCS-5380/5381 series conference unit

Technical Specifications

Electrical

Power supply.....AC 100 V - 240 V, 50 Hz / 60 Hz
 Output.....5 V DC, 2.0 A
 Connector.....UL, CE or VDE type, according to the sales area

Mechanical

Cable length.....1 m
 Dimensions (h x w x d).....43 x 39 x 27 mm
 Weight.....50 g
 Color.....White

Ordering Information

TES-ADP5V.....Power Adapter (5 V DC, 2.0 A, for
 HCS-5380/5381 series conference
 unit)

CBL2SS 2-pin Cable for Conference System



Features

- Connecting HCS-8300KMX with HCS-8300PM/HCS-8300PM2
- Standard connectors (2P aviation socket at each end)
- Length: 1 m

Ordering Information

CBL2SS-01.....1 m 2-pin Cable (with two sockets)
 CBL2SS-01CMP.....1 m 2-pin Cable (with two sockets, CMP)

CBL4PK Power Adapter Cable



Features

- For HCS-8300PM/HCS-8300PM2/HCS-8300KMX or HCS-8600MX supplies power to HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638 series Paperless Multi-media Congress Terminal
- Standard connectors (a 2P aviation socket at one end and a 4P-DIN socket at the opposite end)
- Length: 1 m

Ordering Information

CBL4PK-01CMP.....1 m Power Adapter Cable (for HCS-8300PM/PM2/KMX or HCS-8600MX, supplies power to HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638, CMP)

CBL4PS 4-pin Extension Cable



Features

- Extension cable for connecting HCS-8338 and HCS-8348 series Paperless Multi-media Congress Terminal
- Standard connectors (a plug at one end and a socket at the opposite end)
- Optional: 5 m, 10 m, 20 m, 30 m, 40 m and 50 m available

Ordering Information

CBL4PS-05CMP.....5 m 4-pin Extension Cable (with a plug and a socket, CMP)
 CBL4PS-10CMP.....10 m 4-pin Extension Cable (with a plug and a socket, CMP)
 CBL4PS-20CMP.....20 m 4-pin Extension Cable (with a plug and a socket, CMP)
 CBL4PS-30CMP.....20 m 4-pin Extension Cable (with a plug and a socket, CMP)
 CBL4PS-40CMP.....20 m 4-pin Extension Cable (with a plug and a socket, CMP)
 CBL4PS-50CMP.....50 m 4-pin Extension Cable (with a plug and a socket, CMP)

4-pin Professional Extension Cable for Conference System



Features

- For embedding system cables
- Conductor: 18AWGx4C

Ordering Information

CBL4C-CMP..... Professional Extension Cable for Conference System (4-pin, 18AWGx4C, CMP)

CBL4PT Power Branch Cable



Features

- Power branch cable for "daisy-chain" supplying power to HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638 series Paperless Multi-media Congress Terminal
- Input end: 4P-DIN plug
- Output end: 4P-DIN socket and a DC plug
- Length: 2 m

Ordering Information

CBL4PT-02ACMP..... 2 m Power Branch Cable (for HCS-8338, HCS-8348, HCS-8368, HCS-8668 and HCS-8638 series Paperless Multi-media Congress Terminal, CMP)

Professional Extension Cable for Conference System



Features

- For embedding system cables
- CBLS-UTP: S-UTP Core of Cat.5e Extension Cable :with 4x2x(7x0.2)+96x0.12 Steel wire braided shielding mesh
- CBLS-FTP-CMP: S-FTP Core of Cat.5e Extension Cable :with 4x2x(7x0.2)+96x0.12 Steel wire braided shielding mesh

Ordering Information

CBLS-UTP..... Professional Extension Cable for Conference System

CBLS-FTP-CMP..... Professional Extension Cable for Conference System (CMP)

CBL6PP 6-pin Extension Cable



Features

- Connecting conference main units
- Standard connectors (6P-DIN plug at each end)
- Cable: S-UTP CABLE or FTP CABLE (CMP)
- Cable conductor: 4x2x(7x0.2)+96x0.12
- Length: 2 m
- Used for HCS-3900 series, HCS-4100/50 series and HCS-8300 series

Ordering Information

CBL6PP-02..... 2 m 6-pin Extension Cable (with two plugs)

CBL6PP-02CMP..... 2 m 6-pin Extension Cable (with two plugs, CMP)

CBL6PS 6-pin Extension Cable



Features

- Connecting conference main unit with contribution unit when cable extensions are needed
- Standard connectors (6P-DIN plug and 6P-DIN socket)
- Cable: S-UTP CABLE or FTP CABLE (CMP)
- Cable conductor: 4x2x(7x0.2)+96x0.12
- Optional: 3 m, 5 m, 10 m, 20 m, 30 m, 40 m and 50 m available
- Used for HCS-3900 series, HCS-4100/50 series and HCS-8300 series

Ordering Information

CBL6PS-01	1 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-03	3 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-05	5 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-10	10 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-20	20 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-30	30 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-40	40 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-50	50 m 6-pin Extension Cable (with a plug and a socket)
CBL6PS-03CMP	3 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-05CMP	5 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-10CMP	10 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-20CMP	20 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-30CMP	30 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-40CMP	40 m 6-pin Extension Cable (with a plug and a socket, CMP)
CBL6PS-50CMP	50 m 6-pin Extension Cable (with a plug and a socket, CMP)

CBL5300 Dedicated Transceiver Cable



Features

- Dedicated cable for HCS-5300TD/TDS
- 1 x 6P-DIN male plug
- 1 x 6P-DIN female socket
- Optional: 5 m, 10 m, 20 m, 30 m, 40 m and 50 m available
- Ø 6 mm
- Color: black
- Attention: cable looks identical to CBL6PS but pin-assignment differs!! Please do not mix up!

Ordering Information

CBL5300-05	5 m Dedicated Transceiver Cable
CBL5300-10	10 m Dedicated Transceiver Cable
CBL5300-20	20 m Dedicated Transceiver Cable
CBL5300-30	30 m Dedicated Transceiver Cable
CBL5300-40	40 m Dedicated Transceiver Cable
CBL5300-50	50 m Dedicated Transceiver Cable
CBL5300-05CMP	5 m Dedicated Transceiver Cable (CMP)
CBL5300-10CMP	10 m Dedicated Transceiver Cable (CMP)
CBL5300-20CMP	20 m Dedicated Transceiver Cable (CMP)
CBL5300-30CMP	30 m Dedicated Transceiver Cable (CMP)
CBL5300-40CMP	40 m Dedicated Transceiver Cable (CMP)
CBL5300-50CMP	50 m Dedicated Transceiver Cable (CMP)

Coaxial-cable



Features

- Equivalent impedance: 75 Ohm
- Ø 5 mm (CBLRG-59)
- Ø 7 mm (CBLRG-6/U)
- Length of per roll: 300 meter

Ordering Information

CBLRG-59.....	Coaxial-cable (75 Ω)
CBLRG-6/U.....	Coaxial-cable (75 Ω)

CBL8PS 8-pin Extension Cable



Features

- Connecting conference main unit with contribution unit when cable extensions are needed
- Both ends are 8P-DIN male plug and 8P-DIN female plug
- Cable: S-UTP CABLE or FTP CABLE
- Cable conductor: 4x2x(7x0.2)+96x0.12
- Optional: 3 m, 5 m, 10 m, 20 m, 30 m, 40 m and 50 m available
- Used for HCS-4800 series and HCS-8600 series

Ordering Information

CBL8PS-01.....	1 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-03.....	3 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-05.....	5 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-10.....	10 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-20.....	20 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-30.....	30 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-40.....	40 m 8-pin Extension Cable (with a male plug and a female plug)
CBL8PS-50.....	50 m 8-pin Extension Cable (with a male plug and a female plug)

CBL8PP 8-pin Extension Cable



Features

- Connecting conference main units
- Loop connection for congress units
- Standard connectors (8P-DIN plug at each end)
- Cable: S-UTP CABLE or FTP CABLE
- Cable conductor: 4x2x(7x0.2)+96x0.12
- Length: 2 m
- Used for HCS-4800 series and HCS-8600 series

Ordering Information

CBL8PP-02.....2 m 8-pin Extension Cable (with two male plugs)

**CBL8P2RJ45S
8-pin to RJ45 converter cable**



Features

- Suitable for HCS-4800 series and HCS-8600 series conference systems
- Standard connectors (8P-DIN male plug at one end and a RJ45 socket at the opposite end)
- Cable: FTP CABLE with drain wire
- Length: 1 m

Ordering Information

CBL8P2RJ45S-01.....1 m 8-pin Convert Cable (with an 8-pin male plug and a RJ45 socket, cat.5e Extension Cable with drain wire)

CBL8S2RJ45S
8-pin to RJ45 converter cable



Features

- Suitable for HCS-4800 series and HCS-8600 series conference systems
- Standard connectors (8P-DIN female plug at one end and a RJ45 socket at the opposite end)
- Cable: FTP CABLE with drain wire
- Length: 1 m

Ordering Information

CBL8S2RJ45S-01.....1 m 8-pin Convert Cable (with an 8-pin female plug and a RJ45 socket, cat.5e Extension Cable with drain wire)

CBL8P2RJ45
8-pin to RJ45 converter cable



Features

- Suitable for HCS-4800 series and HCS-8600 series conference systems
- Standard connectors (8P-DIN male plug at one end and a RJ45 plug at the opposite end)
- Cable: FTP CABLE with drain wire
- Length: 1 m

Ordering Information

CBL8P2RJ45-01.....1 m 8-pin Convert Cable (with an 8-pin male plug and a RJ45 plug, cat.5e Extension Cable with drain wire)

CBLRJ45 Ethernet Extension Cable



Features

- Cable: FTP CABLE with drain wire
- Standard connectors (shielded RJ45 plug at each end)
- Cable conductor: 4x2x(7x0.2)+7x0.2
- Metal shield connected with drain wire
- Optional: 3 m, 5 m, 10 m, 20 m, 30 m, 40 m and 50 m available
- Used for HCS-4800 series, HCS-8600 series and education equipment

Ordering Information

CBLRJ45-02.....	2 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-05.....	5 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-10.....	10 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-20.....	20 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-30.....	30 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-40.....	40 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)
CBLRJ45-50.....	50 m Ethernet Extension Cable (with drain wire and shielded RJ45 plugs)

CBLCAT5E



Features

- For embedding system cables
- Cable: FTP CABLE with drain wire
- Cable conductor: 4x2x(7x0.2)+7x0.2
- Length of per roll: 305 meter

Ordering Information

CBLCAT5E.....	Cat.5e Extension Cable (with drain wire, 305 m per roll)
---------------	---

RJ45- PLUG



Features

- For Ethernet cable making
- With metal shield
- Used in conjunction with FTP CABLE with drain wire
- Metal shield connected with drain wire

Ordering Information

RJ45-PLUG.....	Shielded RJ45 plug
----------------	--------------------

BNC-M BNC Connector




Features

- Used to connect HCS-5100M and HCS-5100T or between HCS-5100T
- Used with Coaxial-cable

Ordering Information

BNC-M.....BNC Connector (plug)

HCS-4352T/50 6-pin Cable Splitter



Features

- Relay facility, amplification of the communication signals
- 6P-DIN interfaces, "1 in / 3 out " structure for connection
- 2m-cable with a 6P-DIN connector at the input end
- Three 6PIN output interfaces, can drive 70-meter long extension cable
- Dimensions (h x w x d): 35 x 149 x 90 mm

Ordering Information

HCS-4352T/50.....6-pin Cable Splitter (1 input & 3 outputs, for HCS-4100/50 and HCS-8300 series)

HCS-5352 1x4 Cable Splitter



Features

- Has one in and four out structure
- Each main unit has 6 digital infrared transceiver interfaces, each interface can connect 4 transceivers if operating distributor HCS-5352

Interconnections

- 4 x 6P-DIN sockets
- 2 m cable with 6P-DIN plug

Technical Specifications

Electrical

Voltage33 V DC (supplied from HCS-5300M)
 Number of I/O terminals.....1 in / 4 out

Mechanical

Dimensions (h x w x d).....35 x 149 x 90 mm
 Weight0.32 kg
 Color..... Black

Ordering Information

HCS-5352..... Cable Splitter (1 input & 4 outputs, for HCS-5300T series)

HCS-4353N/06 6-pin Grounding Cable Connection Socket



Features

- For embedding cables to connect conference unit
- For connecting to HCS-3900 series, HCS-4100/50 series or HCS-8300 series conference unit
- Interface: 2 × 6P-DIN female socket
- With 6P-DIN male and female cables for connection to conference systems
- The circuit ground pin of the socket is isolated from the protective earth

Ordering Information

HCS-4353N/06.....6-pin Grounding Cable Connection Socket
(for HCS-3900, HCS-4100/50 and
HCS-8300 series)

Detachable 6P-DIN Standard Plug



Features

- For soldering to 6P-DIN cable
- Removable DIN standard connector (6PIN-DIN)

Ordering Information

DIN-6PM.....Detachable 6P-DIN Standard Plug (male)

Solderable 6P-DIN Standard Socket



Features

- For soldering to 6P-DIN cable
- Solderable 6P-DIN female socket with insulated isolation
- The circuit ground pin of the socket is isolated from the protective earth

Ordering Information

DIN-6SF.....Solderable 6P-DIN Standard Socket (insulating)

Detachable 4P-DIN Standard Plug and Socket



Features

- For soldering to 4P-DIN cable
- Removable DIN standard male connector (4-PIN)

Ordering Information

DIN-4PM.....Detachable 4P-DIN Standard Plug(male)
 DIN-4PF.....Detachable 4P-DIN Standard Plug(female)

Detachable 8P-DIN Standard Plug and Socket



Features

- For soldering to 8P-DIN cable
- Removable DIN standard male connector (8-PIN)

Ordering Information

DIN-8PM.....Detachable 8P-DIN Standard Plug(male)
 DIN-8PF.....Detachable 8P-DIN Standard Plug(female)

Solderable 4P-DIN Standard Socket



Features

- For 4P-DIN extension cable welding
- Solderable 4P-DIN standard socket insulated isolation
- The circuit ground pin of the socket is isolated from the protective earth

Ordering Information

DIN-4SF.....Solderable 4P-DIN Standard Socket (insulating)

Solderable 8P-DIN Standard Socket



Features

- For 8P-DIN extension cable welding
- Solderable 8P-DIN standard socket with insulated isolation
- The circuit ground pin of the socket is isolated from the protective earth

Ordering Information

DIN-8SF.....Solderable 8P-DIN Standard Socket (insulating)

HCS-MES-RCF



Features

- Cabinet installation accessory (mounted in a 19" rack)
- 1U high
- For HCS-8300MES, HCS-8600MES and HCS-3900MES extension unit

Ordering Information

HCS-MES-RCF.....Rack Cabinet Frame (1 HCS-8600MES,
1 HCS-8300MES or 1 HCS-3900MES
Extension Unit can be installed)

**HCS-852KS
Multifunctional Storage Case**



Features

- Used for storing and transporting TAIDEN series products

Technical Specifications

Mechanical

Dimensions h x w x d (mm)
 Outside..... 890 x 760 x 590
 Inside..... 620 x 705 x 535
 Net weight..... 31.0 kg
 Color..... Blue

Ordering Information

HCS-852KS... Multifunctional Storage Case (inner height 620 mm, free fit Foam Insert, holds up to 24 stem microphones in the case cover)

**HCS-852S-CMU
Foam Insert**



Features

- Used to secure Conference System Main Unit and Extension Cable
- Stores up to 1 pc main unit with 2U high + 20-meter extension cable

Technical Specifications

Mechanical

Dimensions h x w x d (mm)..... 118 x 700 x 530
 Net weight..... 1.0 kg
 Color..... Black

Ordering Information

HCS-852S-CMU..... Foam Insert (for 1 pc main unit with 2U high+ 20 m extension cable)

HCS-852S-DStyle Foam Insert



Features

- Used to secure HCS-4330/32 congress units and stem microphones
- Stores up to 12 pcs HCS-4330/32 congress units + 8 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....100 x 700 x 530
 Net weight.....0.9 kg
 Color.....Black

Ordering Information

HCS-852S-Dstyle.....Foam Insert (for 12 pcs HCS-4330/32 + 8 pcs stem microphones)

HCS-852S-GStyle Foam Insert



Features

- Used to secure HCS-4886/87/88 congress units and stem microphones
- Stores up to 10 pcs HCS-4886/87/88 congress units + 6 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....150 x 700 x 530
 Net weight.....1.0 kg
 Color.....Black

Ordering Information

HCS-852S-Gstyle.....Foam Insert (for 10 pcs HCS-4886/87/88 + 6 pcs stem microphones)

**HCS-852S-1U
Foam Insert**



Features

- Used to secure 2 pcs devices of 1U height and attached cables
- Stores up to 2 pcs devices of 1U height and attached cables

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....55 x 700 x 530
 Net weight.....0.7 kg
 Color.....Black

Ordering Information

HCS-852S-1U.....Foam Insert (for 2 pcs devices of 1U height and attached cables)

**HCS-852S-4338
Foam Insert**



Features

- Used to secure HCS-3638/HCS-4338/HCS-3938 conference units, stem microphones and attached cables
- Stores up to 16 pcs HCS-3638/HCS-4338/HCS-3938 conference units + 10 pcs stem microphones + attached cables

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....150 x 700 x 530
 Net weight.....1.0 kg
 Color.....Black

Ordering Information

HCS-852S-4338.....Foam Insert (for 16 pcs HCS-3638/HCS-4338/HCS-3938 + 10 pcs stem microphones + attached cables)

**HCS-852S-4385U
Foam Insert**



Features

- Used to secure HCS-4385U/50 interpreter units and stem microphones
- Stores up to 6 pcs HCS-4385U/50 interpreter units + 2 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....100 x 700 x 530
 Net weight.....0.9 kg
 Color.....Black

Ordering Information

HCS-852S-4385U.....Foam Insert (for 6 pcs HCS-4385U/50 + 2 pcs stem microphones)

**HCS-852S-5100T
Foam Insert**



Features

- Used to secure HCS-5100T Digital Infrared Radiator and HCS-4385U/50 Interpreter Units
- Stores up to 1 pc HCS-5100T + 2 pcs HCS-4385U/50

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....200 x 700 x 530
 Net weight.....1.6 kg
 Color.....Black

Ordering Information

HCS-852S-5100T.....Foam Insert (for 1 pc HCS-5100T + 2 pcs HCS-4385U/50)

**HCS-852S-5300CHG
Foam Insert**



Features

- Used to secure HCS-5300CHG/08 Charging Units
- Stores up to 2 pcs HCS-5300CHG/08

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....100 x 700 x 530
 Net weight.....1.0 kg
 Color.....Black

Ordering Information

HCS-852S-5300CHG.....Foam Insert (for 2 pcs HCS-5300CHG/08)

**HCS-852S-5300D
Foam Insert**



Features

- Used to secure HCS-5300 Series Digital Infrared Wireless Conference Units
- Stores up to 8 pcs HCS-5300 Digital Infrared Wireless Conference Units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....100 x 700 x 530
 Net weight.....1.0 kg
 Color.....Black

Ordering Information

HCS-852S-5300D.....Foam Insert (for 8 pcs HCS-5300 wireless conference units)

**HCS-852S-5300TD
Foam Insert**



Features

- Used to secure HCS-5300CHG/08 Charging Unit and HCS-5300TD Digital Infrared Transceiver
- Stores up to 1 pc HCS-5300CHG/08 + 2 pcs HCS-5300TD

Technical Specifications


Mechanical

Dimensions h x w x d (mm).....100 x 700 x 530
 Net weight.....1.0 kg
 Color.....Black

Ordering Information

HCS-852S-5300TD.....Foam Insert (for 1 pc HCS-5300CHG/08 + 2 pcs HCS-5300TD)

**HCS-852S-8338
Foam Insert**



Features

- Used to secure HCS-8338/HCS-8335 Multimedia Congress Terminals
- Stores up to 4 pcs HCS-8338/HCS-8335 Multimedia Congress Terminals

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....180 x 700 x 530
 Net weight.....1.2 kg
 Color.....Black

Ordering Information

HCS-852S-8338.....Foam Insert (for 4 pcs HCS-8338/HCS-8335/HCS-8336 series Congress Terminals)

**HCS-852S-4860
Foam Insert**



Features

- Used to secure HCS-4860 series congress units
- Stores up to 8 pcs HCS-4860 series congress units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....140 x 700 x 530
 Net weight.....1.6 kg
 Color.....Black

Ordering Information

HCS-852S-4860.....Foam Insert (for 8 pcs HCS-4860 series congress units)

**HCS-852S-4866
Foam Insert**



Features

- Used to secure HCS-4866/50 series congress units
- Stores up to 8 pcs HCS-4866/50 series congress units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....150 x 700 x 530
 Net weight.....1.6 kg
 Color.....Black

Ordering Information

HCS-852S-4866.....Foam Insert (for 8 pcs HCS-4866/50 series congress units)

**HCS-852S-4890
Foam Insert**



Features

- Used to secure HCS-4890/50 series congress units and stem microphones
- Stores up to 12 pcs HCS-4890/50 series congress units + 12 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....130 x 700 x 530
 Net weight.....1.3 kg
 Color.....Black

Ordering Information

HCS-852S-4890.....Foam Insert (for 12 pcs HCS-4890/50 series congress units + 12 pcs stem microphones)

**HCS-852S-4891R
Foam Insert**



Features

- Used to secure HCS-4891R/50/(2M) series congress units
- Stores up to 8 pcs HCS-4891R/50/(2M) series congress units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....130 x 700 x 530
 Net weight.....1.3 kg
 Color.....Black

Ordering Information

HCS-852S-4891R.....Foam Insert (for 8 pcs HCS-4891R/50/(2M) series congress units)

**HCS-852S-8368A
Foam Insert**



Features

- Used to secure HCS-8368A/50 series tabletop Multimedia Congress Terminals
- Stores up to 5 pcs HCS-8368A/50 series tabletop Multimedia Congress Terminals

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....225 x 700 x 530
 Net weight.....1.4 kg
 Color.....Black

Ordering Information

HCS-852S-8368A.....Foam Insert (for 5 pcs HCS-8368A/50 series tabletop Congress Terminals)

**HCS-852S-8385
Foam Insert**



Features

- Used to secure HCS-8385/80 and HCS-8685 interpreter units
- Stores up to 6 pcs HCS-8385/80 or HCS-8685 interpreter units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....120 x 700 x 530
 Net weight.....1.2 kg
 Color.....Black

Ordering Information

HCS-852S-8385.....Foam Insert (for 6 pcs HCS-8385/80 or HCS-8685 interpreter units)

HCS-853KS Transport Cabinet



Features

- Used for storing and transporting TAIDEN series main units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....890 x 590 x 545
 Net weight.....33.7 kg
 Color.....Blue

Ordering Information

HCS-853KS.....Transport Cabinet (inner height 15U)

HCS-854KS

Portable Multifunctional Storage Case



Features

- Used for storing and transporting TAIDEN series products

Technical Specifications

Mechanical

Dimensions h x w x d (mm)

Outside.....	338 x 663 x 496
Inside.....	299 x 575 x 406
Net weight.....	10.5 kg
Color.....	Black

Ordering Information

HCS-854KS..... Portable Multifunctional Storage Case
(inner height 299 mm, free fit Foam Insert)



**HCS-854S-CMU
Foam Insert**



Features

- Used to secure Conference System Main Unit
- Stores up to 1 pc main unit with 2U high

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....118 x 573 x 408
 Net weight.....0.6 kg
 Color.....Black

Ordering Information

HCS-854S-CMU.....Foam Insert (for 1 pc main unit with 2U high)

**HCS-854S-MIC
Foam Insert**



Features

- Used to secure stem microphones
- Stores up to 11 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....55 x 573 x 408
 Net weight.....0.6 kg
 Color.....Black

Ordering Information

HCS-854S-MIC.....Foam Insert (for 11 pcs stem microphones)

**HCS-8524S-4338
Foam Insert**



Features

- Used to secure HCS-3638/HCS-4338 conference units
- Stores up to 10 pcs HCS-3638/HCS-4338 conference units

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....120 x 573 x 408
 Net weight.....0.7 kg
 Color.....Black

Ordering Information

HCS-854S-4338.....Foam Insert (for 10 pcs HCS-3638/HCS-4338)

**HCS-854S-4385U
Foam Insert**



Features

- Used to secure HCS-4385U/50 interpreter units and stem microphones
- Stores up to 3 pcs HCS-4385U/50 interpreter units + 4 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....98 x 573 x 408
 Net weight.....0.6 kg
 Color.....Black

Ordering Information

HCS-854S-4385U.....Foam Insert (for 3 pcs HCS-4385U/50 + 4 pcs stem microphones)

HCS-854S-4886 Foam Insert



Features

- Used to secure HCS-4886/87/88 congress units and stem microphones
- Stores up to 3 pcs HCS-4886/87/88 congress units + 4 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....98 x 573 x 408
 Net weight.....0.7 kg
 Color.....Black

Ordering Information

HCS-854S-4886.....Foam Insert (for 3 pcs HCS-4886/87/88 + 4 pcs stem microphones)

HCS-854S-8338 Foam Insert



Features

- Used to secure HCS-8338/HCS-8335 Multimedia Congress Terminals
- Stores up to 3 pcs HCS-8338/HCS-8335 Multimedia Congress Terminals

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....180 x 573 x 408
Net weight.....0.8 kg
Color.....Black

Ordering Information

HCS-854S-8338.....Foam Insert (for 3 pcs HCS-8338/HCS-8335/
HCS-8336 series Congress Terminals)

**HCS-854S-5100T
Foam Insert**



Features

- Used to secure HCS-5100T Digital Infrared Radiator
- Stores up to 1 pc HCS-5100T

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....178 x 573 x 408
 Net weight.....0.9 kg
 Color.....Black

Ordering Information

HCS-854S-5100T.....Foam Insert (for 1 pc HCS-5100T)

**HCS-854S-5300
Foam Insert**



Features

- Used to secure HCS-5300 wireless conference units and stem microphones
- Stores up to 4 pcs HCS-5300 wireless conference units + 4 pcs stem microphones

Technical Specifications

Mechanical

Dimensions h x w x d (mm).....98 x 573 x 408
 Net weight.....0.7 kg
 Color.....Black

Ordering Information

HCS-854S-5300.....Foam Insert (for 4 pcs HCS-5300 wireless conference units + 4 pcs stem microphones)

HCS-851A/02 Interpreter Booth



HCS-851A/02



HCS-851K

Features

- Compliant to ISO 4043 and GB 50524-2010
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.20 m), opens outwards, operates silently
- Two front windows and two side windows (high: 0.87 m); lower edge of the window: 0.79 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: ≥24 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Ventilation system (purging 8 times per hour at least) of interpretation booth uses low-noise exhaust fan
- Internal dimensions of the booth h × w × d (cm): 200 × 160 × 160, accommodates two interpreters
- Overall dimensions of the booth h × w × d (cm): 204 × 172 × 172
- Shipping needs HCS-851K Interpreter Booth Shipping Case
 - ◆ Dimensions of HCS-851K h × w × d (cm): 110×209×79
 - ◆ Weight (incl. the booth): 260 kg

Ordering Information

HCS-851A/02..... Interpreter Booth (accommodates 2 interpreters, internal dimensions is 200×160×160 cm, aluminum alloy framework convenience for disassembly, with a shipping case, total weight is 260 kg)

HCS-851K.....Interpreter Booth Shipping Case (for HCS-851A/02)

HCS-851A/03 Interpreter Booth



HCS-851A/03



HCS-851K



HCS-851KT

Features

- Compliant to ISO 4043 and GB 50524-2010
- Odorless, antistatic, fire-retardant material
- Optimum insulation and sound absorption
- Hinged door (with observation window 0.20 m × 0.20 m), opens outwards, operates silently
- Three front windows and two side windows (high: 0.87 m); lower edge of the window: 0.79 m from booth floor
- Booth to hall (and vice versa) - sound pressure level difference: ≥24 dB (1 kHz)
- Reverberation time inside the booth: between 0.3 and 0.5 s (octave bands from 125 Hz to 4000 Hz, booth unoccupied)
- Ventilation system (purging 8 times per hour at least) of interpretation booth uses low-noise exhaust fan
- Internal dimensions h × w × d (cm): 200×240×160, accommodates three interpreters
- Overall dimensions h × w × d (cm): 204×252×172
- Shipping needs HCS-851K and HCS-851KT Interpreter Booth Shipping Case
 - ♦ Dimensions of HCS-851K h × w × d (cm): 110×75×209
 - ♦ Dimensions of HCS-851KT h × w × d (cm): 91×215×40
 - ♦ Weight (incl. the booth): 350 kg

Ordering Information

HCS-851A/03,..... Interpreter Booth (accommodates 3 interpreters, internal dimensions is 200×240×160 cm, aluminum alloy framework convenience for disassembly, with 2 shipping case, total weight is 350kg)

HCS-851KT.....Interpreter Booth Shipping Case
(for HCS-851A/03, HCS-851K needed)